

Trans Mountain Pipeline Published Receipt Qualities

June 8, 2026

Company: Gibson Edmonton Terminal

Trans Mountain Pipeline receipt qualities for the month of :

May-26

RMHG

Month	Absolute Density Wt Avg. (kg/m ³)	S&W (vol%)	Total Sulfur (wt%)	H ₂ S (wt ppm)	VPCR ₄ (37.8°C) (kPa)	Kinematic Viscosity 1st Half Month @ Ref cSt	Kinematic Viscosity 2nd Half Month @ Ref cSt	TAN (mg KOH/g)	MCR (wt %)
May-26	919.0	0.389	3.99	-	69	337.76	343.36	1.90	10.23

6 Month Historical Quality Data for Product Stream: RMHG

Month	Absolute Density Wt Avg. (kg/m ³)	S&W (vol%)	Total Sulfur (wt%)	H ₂ S (wt ppm)	VPCR ₄ (37.8°C) (kPa)	Kinematic Viscosity 1st Half Month @ Ref cSt	Kinematic Viscosity 2nd Half Month @ Ref cSt	TAN (mg KOH/g)	MCR (wt %)
Dec-25	918.3	0.402	4.26	-	66.7	318.5	336.1	1.80	10.05
Jan-26	915.9	0.387	4.14	-	67.4	334.8	321.0	1.80	10.09
Feb-26	916.1	0.369	3.94	-	76.2	333.9	317.9	1.85	10.06
Mar-26	915.5	0.377	3.85	-	67.6	330.4	339.0	1.85	10.17
Apr-26	915.6	0.383	3.92	-	67.5	318.9	303.5	1.95	10.19
May-26	919.0	0.389	3.99	-	69.1	337.8	343.4	1.90	10.23

Absolute Density is a monthly weighted average calculation from individual tickets. Value on this report may not match densities on actual tickets.

S&W (ASTM D4928 and ASTM D4807) is a monthly weighted average calculated from individual ticketed values. Value on this report may not match S&W on actual tickets.

Total Sulphur (ASTM D4294) is measured monthly from composite samples.

H₂S (UOP 163) is measured either monthly or quarterly from spot samples taken on receipt.

VPCR₄(37.8°C) (ASTM D6377) is measured either monthly or quarterly from spot samples taken on receipt.

Kinematic Viscosity (ASTM D7042) is measured from a spot sample every two weeks in accordance with changing Reference Temperatures.

TAN (ASTM D664) is measured monthly from composite samples.

MCR (ASTMD4530) is measured monthly from composite samples.

- Indicates No Data